



Product Data Sheet (PDS)

KI- 222 SF

Spotting Fluid (Weighted)

PRODUCT FEATURES:

It is special blend of surface active agent, emulsifier, wetting agent and wall cake cracking material for making up a complete oil base spotting system.

PRODUCT DESCRIPTION:

KI- 222 SF may be used in diesel oil crude or low toxicity oil. Does not required high shear and long mixing time. Allow quick and effective operation in case of stuck pipe problems. It can be weighted up to the desire drilling fluid density. It may be incorporated in to drilling fluid after pipe is free.

TYPICAL SPECIFICATIONS :

Appearance	Blakish Brown Oily Liquid
Sp. gravity @ 20 °C	➤ 1 g/cc.
Solubility	Soluble in Water & Partially in HSD

APPLICATION :

KI-222 SF dehydrate wall cake, allowing penetration of the spotting fluid and wetting of the drill stream. Reducing the forces of cohesion between the pipe and care, resulting freeness of pipe. It is advisable to contact our Technical Representative for evaluation of the system prior to application of the corrosion inhibitor.

SAFETY / PACKING :

KI- 222 SF is available in 250 kg drums and in bulk packing on special request. Safe Handling of **KI-222 SF** is recommended in MSDS which is available on request.