



KI OILFIELD CHEMICALS PRIVATE LIMITED

Product Data Sheet (PDS)

KI-32

Demulsifier

PRODUCT FEATURES:

Demulsifier is formulated for treatment of Oil and Water Emulsion providing a sharp interface and clear water.

PRODUCT DESCRIPTION:

KI 32 Demulsifier is a synergetic blend of give maximum reduction in surface tension and demulsification to well simulated fluids, in addition to aiding in prevention or destruction of damaging emulsions. Product is stable for more than 1 year.

APPLICATION :

KI-32 Demulsifier is recommended to be applied with the help of chemical injection pump at the inlet to the facility, and should be continuously injected at a rate of 25 ~ 100 ppm. However, field testing of the product need to be performed to determine the optimum treating rate required to produce clean oil. It is advisable to contact our Technical Representative for evaluation of the system prior to application of the corrosion inhibitor.

TYPICAL SPECIFICATIONS :

Appearance @ 20°C	Yellow to Brown Liquid
Sp. gravity @ 20 °C	0.900 ± 0.05 g/cc
Solubility	Soluble in Crude Oil, Xylene, Toluene.

SAFETY/PACKING :

KI- 32 Demulsifier is a Flammable Liquid. It is available in 200 liter drums and in bulk packing on special request. Safe Handling of **KI-32** is recommended in MSDS which is available on request.